



Herмоса 2-Pack Epoxy Floor Paint

Technical Data Sheet



Hermosa 2 Pack Epoxy Floor Paint

Technical Data Sheet



General Product Description

Hermosa 2 Pack Epoxy Floor Paint is high performance two component epoxy based floor paint cured by epoxy hardener. It is ideal for application in chemical plants, factories and other high traffic areas.

Product Information

Technical Data

Technical Data	
Finish	Gloss, Satin
Application	Apply 2- 3 coats at 16 hours intervals.
Drying time	Touch dry 2-4 hours. Hard dry 16 hours Re-coatable overnight. Maximum hardness in 7 days.
Spreading per Coat	Approximately 10 square metres per litre.
Equipment Cleaning	Use Hermosa 2 pack Epoxy Thinner.
Surface preparation	Remove any loose and flaking materials, repair cracks and level the surface. Clean the surface and ensure they are dry and free from dust, oil and grease. Apply 2-3 coats of Hermosa 2 Pack Epoxy Floor Paint.
Mixing	Mix 3 parts of Hermosa Epoxy floor paint with 1 part of epoxy hardener. Mix material to be used in less than 6 hours. Thin to the required viscosity with Hermosa Epoxy Thinner.
Application	New primed metal, wood, plaster : Do proper surface preparation. Apply 1 coat Hermosa Universal Undercoat over the appropriate primer. Allow 16 hours drying before overcoating with the desired finish. Previously painted - unsound surfaces : Remove any loose or flaky materials Ensure surface is clean, dry and free of other defects. Patch prime bare surfaces with appropriate primer. Apply 1 coat Hermosa Universal Undercoat. Previously painted - sound surfaces: Lightly abrade and ensure the surface is clean. Apply 1 coat Hermosa Universal Undercoat.
Storage	Store in a cool dry place at average room temperatures.

Hermosa Paints Limited

📍 P.O Box: 78895-00507, Nairobi Kenya.

📞 Mobile: 0794 899 999

📞 Customer care: 0759 111 333

✉ Email: sales@hermosapaints.com

📍 Location : HighPort Properties, Road C Industrial area.

🌐 Website: www.hermosapaints.com



Hermosa 2 Pack Epoxy Floor Paint

Technical Data Sheet



For health and safety information, please refer to our Product Material Safety Data Sheet.

Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by Hermosa paints. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Hermosa paints representative to obtain the most recent Product Data Information

Herмоса Paints Limited

✉ P.O Box: 78895-00507, Nairobi Kenya.

📞 Mobile: 0794 899 999

📞 Customer care: 0759 111 333

✉ Email: sales@hermosapaints.com

📍 Location : HighPort Properties, Road C Industrial area.

🌐 Website: www.hermosapaints.com



Unleashing Colours, Brightening Lives

Hermosa Paints Limited

- ✉ P.O Box: 78895-00507, Nairobi Kenya.
- 📞 Mobile: 0794 899 999
- 📞 Customer care: 0759 111 333
- ✉ Email: sales@hermosapaints.com
- 📍 Location : HighPort Properties,
Road C Industrial area.
- 🌐 Website: www.hermosapaints.com

