



Unleashing Colours, Brightening Lives



Acrylic Sealer Undercoat

Technical Data Sheet



Acrylic Sealer Undercoat

Technical Data Sheet



General Product Description

Hermosa Acrylic Sealer Undercoat is a premium emulsion-based undercoat specially formulated for the interior and exterior use on walls and ceilings. It can be applied directly on plaster, soft board surfaces, cement rendering, brick and stones. Has high opacity and good adhesion on substrate materials.

Product Information

Technical Data

Finish	Matt, high-built texture
Spread Rate per coat	10-12 Square meters/litre on smooth and skimmed surfaces.
Drying time	Touch dry 1/2 hour. Hard dry and re-coatable after 3-4 hours
Application Tools	By Brush, Rollers, airless Spray .
Thinning	Clean water.
Color Range	White. Other colors can be made on request.
Cleaning	water.
Pack sizes	1 litre, 4 litres and 20 litres.
Surface preparation	<ul style="list-style-type: none">Prepare the surface properly. Cracks and surface defects should be filled using Hermosa Skim Coat Filler and smoothly sanded . Apply 1-2 coats of Hermosa Acrylic Sealer Undercoat. Not recommended for surfaces previously painted with gloss paints.
Storage	<ul style="list-style-type: none">Store in a cool dry place at average room temperatures.

Hermosa Paints Limited

☎ P.O Box: 78895-00507, Nairobi Kenya.

☎ Mobile: 0794 899 999

☎ Customer care: 0759 111 333

✉ Email: sales@hermosapaints.com

📍 Location : HighPort Properties, Road C Industrial area.

🌐 Website: www.hermosapaints.com



Unleashing Colours, Brightening Lives

Hermosa Paints Limited

- ✉ P.O Box: 78895-00507, Nairobi Kenya.
- 📱 Mobile: 0794 899 999
- 📞 Customer care: 0759 111 333
- ✉ Email: sales@hermosapaints.com
- 📍 Location : HighPort Properties,
Road C Industrial area.
- 🌐 Website: www.hermosapaints.com

