



HERMOSA PAINTS

Unleashing Colours, Brightening Lives



Hermosa Rough Master Texture

Technical Data Sheet



Hermosa Rough Master Texture

Technical Data Sheet



General Product Description

Hermosa Rough Master Texture is an exterior texture coating with excellent durability on concrete & plastered surfaces.

It is skillfully formulated with unique extenders & pigments, special additives & a novel emulsion to provide remarkable weatherability & first-class texture of its own.

Features & Benefits

- Interior and exterior usage.
- Has -15year warranty.
- Can be made multiple directional texture designs.
- Prevents walls from mould and algae attacks.
- Can be top-coated with corresponding interior or exterior paints.

Product Information

Technical Data

Finish	Matt, high-built texture
Spread Rate per coat	Approximately 9-11 sq. Metre per 30kgs depending on dry film thickness.
Drying time	<ul style="list-style-type: none">• Surface dry: after 4 hrs., hard dry: after 24 hrs.• Achieves Maximum Hardness in 7 Days
Application Tools	Stainless steel trowel and plastic trowel.
Thinning	Its ready for use but if need be, thin with a small amount of water.
Color Range	Available in a wide range of colors. Special colors can be made on request.
Cleaning	Clean with water after use.
Pack sizes	5Kgs,30Kgs
Surface preparation	<ul style="list-style-type: none">• New walls: prepare the surfaces properly and apply Hermosa Acrylic Sealer Undercoat before applying Hermosa Rough Master Texture.• On previously painted sound surfaces: remove completely any deteriorated coats of old paint by scraping and wire brushing and any large cracks should be filled with a hard filler or cement and allowed to dry prior to applying Hermosa Rough Master Texture.

Hermosa Paints Limited

☎ P.O Box: 78895-00507, Nairobi Kenya.

📞 Mobile: 0794 899 999

📞 Customer care: 0759 111 333

✉ Email: sales@hermosapaints.com

📍 Location : HighPort Properties, Road C Industrial area.

🌐 Website: www.hermosapaints.com



Hermosa Rough Master Texture

Technical Data Sheet



Technical Data

Storage

- Store in a cool dry place at average room temperatures.

Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by Hermosa paints. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Hermosa paints representative to obtain the most recent Product Data Information

Herмоса Paints Limited

📍 P.O Box: 78895-00507, Nairobi Kenya.

📞 Mobile: 0794 899 999

📞 Customer care: 0759 111 333

✉ Email: sales@hermosapaints.com

📍 Location : HighPort Properties, Road C Industrial area.

🌐 Website: www.hermosapaints.com



Unleashing Colours, Brightening Lives

Hermosa Paints Limited

- ✉ P.O Box: 78895-00507, Nairobi Kenya.
- 📞 Mobile: 0794 899 999
- 📞 Customer care: 0759 111 333
- ✉ Email: sales@hermosapaints.com
- 📍 Location : HighPort Properties,
Road C Industrial area.
- 🌐 Website: www.hermosapaints.com

