



HERMOSA PAINTS

Unleashing Colours, Brightening Lives



Hermosa Stucco Smoother

Technical Data Sheet



Hermosa Stucco Smoother

Technical Data Sheet



General Product Description

Hermosa Stucco Smoother is a ready mixed surfacing compound for cement plaster surfaces, appropriately primed wooden surfaces and ceiling boards, hardwood and softwood. It is based on selected fillers and resin and gives excellent smoothness. Different texture effects can be achieved by using different application techniques. It is used for smoothing uneven plasterwork.

Features & Benefits

- Easy to apply and economical.
- Washable and dirt repellent film.
- Water thinnable.

Product Information

Technical Data

Finish	Matt
Application Tools	By Spatula, Trowel
Thinning	Supplied ready for use.
Cleaning	Clean equipment with water
Thinning	Its ready for use but if need be, thin with a small amount of water.
Color Range	White
Cleaning	Clean with water after use.
Drying Time	Touch Dry: 40 minutes. Hard Dry: 8 - 10 hours
Spread Rate	<ul style="list-style-type: none">• Approximately 1kg per Sq. Meter. May vary depending on application thickness, and texture of substrate
Film Thickness	<ul style="list-style-type: none">• Should be kept at an average of 1.0mm as applications whose thickness is over 1.5mm may lead to cracking.• Storage: Store in a cool dry place at average .
Storage	<ul style="list-style-type: none">• Store in a cool dry place at average room temperatures.

Hermosa Paints Limited

☎ P.O Box: 78895-00507, Nairobi Kenya.
📱 Mobile: 0794 899 999
🗨 Customer care: 0759 111 333

✉ Email: sales@hermosapaints.com
📍 Location : HighPort Properties, Road C Industrial area.
🌐 Website: www.hermosapaints.com



Hermosa Stucco Smoother

Technical Data Sheet



Technical Data

Application

- New and Old Cement Plaster surfaces: Surface must be dry and free of loose material. Apply appropriate primer first. Apply one coat of Hermosa Stucco smoother on all joints and about 200mm on each side of joint. Allow to dry hard and smoothen with sand-paper. If joint is too wide on plaster boards, fix with fiberglass scrim. Apply second coat of Hermosa Stucco Smoother, leveling out to smooth surface or desired hard pattern on final coat ready for decoration allowing hard drying in between coats.
- Block-boards, Ceiling-boards, Hard and Soft wood surfaces: Surface must be appropriately primed with Hermosa Acrylic Sealer Undercoat, application of Hermosa Vinyl matt to reduce on absorbance. Follow the same procedure as in cement Plaster surfaces above
- Brick and Asbestos surfaces: Same procedure as in Cement Plaster surfaces.

Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by Hermosa paints. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Hermosa paints representative to obtain the most recent Product Data Information

Hermosa Paints Limited

☎ P.O Box: 78895-00507, Nairobi Kenya.

☎ Mobile: 0794 899 999

☎ Customer care: 0759 111 333

✉ Email: sales@hermosapaints.com

📍 Location : HighPort Properties, Road C Industrial area.

🌐 Website: www.hermosapaints.com



Unleashing Colours, Brightening Lives

Hermosa Paints Limited

- ✉ P.O Box: 78895-00507, Nairobi Kenya.
- 📱 Mobile: 0794 899 999
- 📞 Customer care: 0759 111 333
- ✉ Email: sales@hermosapaints.com
- 📍 Location : HighPort Properties,
Road C Industrial area.
- 🌐 Website: www.hermosapaints.com

