



Unleashing Colours, Brightening Lives



Herмоса Self-Priming Roof Paint

Technical Data Sheet



Hermosa Self-Priming Roof Paint

Technical Data Sheet



General Product Description

Hermosa Self-Priming Roof Paint is an emulsion paint based on special PVA to give maximum protection on galvanized iron sheets and concrete roofs.

Product Information

Technical Data	
Thinning and Mixing	Ready for use but if need be thin with little amount of water.
Finish	Semi-Matt
Drying	Recoatable after 3-4 hours
Application	By brush, or airless-spray. Ensure surface is free from rust, loose and flaky materials. Apply 1-2 coats of Hermosa Self Priming roof paint.
Spreading Capacity per Coat	10-12 Square metre per litre
Equipment Cleaning	clean equipment immediately after use with clean water.
Advantages:	Roofs decorated and protected with Hermosa Self-Priming roof paint collect rain water that is clean for human consumption. Its flexible and very durable in all weather conditions.
Storage	Store in a cool dry place at average room temperatures.

For health and safety information, please refer to our Product Material Safety Data Sheet.



Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by Hermosa paints. Such information and recommendations set forth herein are subject to change and pertain to the product

Hermosa Paints Limited

☎ P.O Box: 78895-00507, Nairobi Kenya.
📞 Mobile: 0794 899 999
🗨 Customer care: 0759 111 333

✉ Email: sales@hermosapaints.com
📍 Location : HighPort Properties, Road C Industrial area.
🌐 Website: www.hermosapaints.com



Unleashing Colours, Brightening Lives

Hermosa Paints Limited

- ✉ P.O Box: 78895-00507, Nairobi Kenya.
- 📞 Mobile: 0794 899 999
- 📞 Customer care: 0759 111 333
- ✉ Email: sales@hermosapaints.com
- 📍 Location : HighPort Properties,
Road C Industrial area.
- 🌐 Website: www.hermosapaints.com

