



Unleashing Colours, Brightening Lives



Herмоса Metal Putty

Technical Data Sheet



Hermosa Metal Putty

Technical Data Sheet



General Product Description

Hermosa Metal Putty is used for the glazing of wooden and metal window frames with single glass. It is suitable for use in bedding and external fronting of single glass into primed softwood and hardwood frames. Can also be used to glaze single glass into concrete or stone surrounds after prior sealing with an appropriate sealer. It is easy to apply and budget friendly. Features & Benefits

Product Information

Technical Data	
Finish	Matt
Application Tools	By palette knife or blade
Thinning	Ready to apply but, if need be, you can thin with small quantity of Hermosa Mineral Turpentine.
Spreading Capacity	1Kg will glaze approximately 4 linear meters of glass.
Drying Times	Skin formation takes approximately 2-4days outdoors dependent on ambient temperature and humidity. Can take up to 2 months to fully cure based on the prevailing weather conditions.
Equipment Cleaner:	Hermosa White Spirit.
Color:	White, Grey.
Surface Preparation	Remove all dirt, grease and loose material from the rebate. Make sure the timber is dry and moisture free.
Application	Check the condition of the primer or stain on softwood timber frames, especially the rebate and glazing surface of the beads. Any section which has been partially missed or is considerably weathered should be reprimed before glazing. When using as back bedding, apply to rebate. Push in glass and leave a thickness of 1.5mm by 2mm so as to achieve sufficient load bearing properties. The maximum fillet size to allow correct setting is 15mm high x 25mm wide. Do not reduce the fillet size below 8mm high x 10mm wide.
Finishing	The putty must be painted as soon as it has formed a skin firm enough to accept the actions of over coating. Apply the first coat usually within 7 to 21 days. The final coat should be applied within 28 days.
Health and Safety	Keep away from children. Clean hands after use. Refer to safety data sheet for safe use and disposal.

Hermosa Paints Limited

📍 P.O Box: 78895-00507, Nairobi Kenya.

📞 Mobile: 0794 899 999

📞 Customer care: 0759 111 333

✉ Email: sales@hermosapaints.com

📍 Location : HighPort Properties, Road C Industrial area.

🌐 Website: www.hermosapaints.com



Hermosa Metal Putty

Technical Data Sheet



Technical Data

Storage

- Store in a cool dry place at average room temperatures.

Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by Hermosa paints. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Hermosa paints representative to obtain the most recent Product Data Information

Hermosa Paints Limited

📍 P.O Box: 78895-00507, Nairobi Kenya.

📞 Mobile: 0794 899 999

📞 Customer care: 0759 111 333

✉ Email: sales@hermosapaints.com

📍 Location : HighPort Properties, Road C Industrial area.

🌐 Website: www.hermosapaints.com



Unleashing Colours, Brightening Lives

Hermosa Paints Limited

- ✉ P.O Box: 78895-00507, Nairobi Kenya.
- 📱 Mobile: 0794 899 999
- 📞 Customer care: 0759 111 333
- ✉ Email: sales@hermosapaints.com
- 📍 Location : HighPort Properties,
Road C Industrial area.
- 🌐 Website: www.hermosapaints.com

