



HERMOSA PAINTS

Unleashing Colours, Brightening Lives



Hermosa Eco-Plast Emulsion Paint

Technical Data Sheet



Hermosa Eco-Plast Emulsion Paint

Technical Data Sheet



General Product Description

Hermosa Eco-Plast Emulsion is an economical emulsion based specially formulated for the interior use on walls and ceilings. It can be applied directly to plaster, soft board surfaces, cement rendering, brick and stone.

Surface preparation: Remove any loose and flaking materials. Clean walls and stones, ensure they are dry and free from dust. Apply 2-1 coats of Hermosa Eco-Plast Emulsion.

Product Information

Technical Data	
Finish	Matt
Spread Rate per coat	8-10sq metres/litre on smooth and skimmed surfaces
Drying time	Touch dry 1 hour, Hard dry and recoatable 4hours
Application Tools	By Brush, Rollers, airless Spray
Thinning	Thinning
Cleaning	Clean with water after use.
Pack sizes	1ltr, 4 ltrs, 20 ltrs
Storage	<ul style="list-style-type: none">Store in a cool dry place at average room temperatures.

Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by Hermosa paints. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Hermosa paints representative to obtain the most recent Product Data Information

Hermosa Paints Limited

☎ P.O Box: 78895-00507, Nairobi Kenya.

☎ Mobile: 0794 899 999

☎ Customer care: 0759 111 333

✉ Email: sales@hermosapaints.com

📍 Location : HighPort Properties, Road C Industrial area.

🌐 Website: www.hermosapaints.com



Unleashing Colours, Brightening Lives

Hermosa Paints Limited

- ✉ P.O Box: 78895-00507, Nairobi Kenya.
- 📞 Mobile: 0794 899 999
- 📞 Customer care: 0759 111 333
- ✉ Email: sales@hermosapaints.com
- 📍 Location : HighPort Properties,
Road C Industrial area.
- 🌐 Website: www.hermosapaints.com

